



FENCE WIRE SLEEVES AND TOOLS—DATA SHEET
 FOR PRODUCTS IN NICOPRESS CATALOG NO. F-16

LAP TYPE FENCE WIRE SLEEVES AND TOOLS					
NICOPRESS® SLEEVE SELECTION				NICOPRESS® TOOLS	
METRIC WIRE SIZE (mm)	WIRE SIZE	SLEEVE STOCK NUMBER	APPROX. WT (Kg) BOX OF 100	TOOL GROOVE	TOOLS
4.5 mm	7 gauge	FW-5-6	2.1	FW-5-6	3-56
3.7 mm	9 gauge	FW-4-5	1.0	FW-4-5	64-2345
3.4 mm	10 gauge	FW-3-4	0.8	FW-3-4	64-2345
3.0 mm	11 gauge	FW-3-4	0.8	FW-3-4	64-2345
2.5 mm	12-1/2 gauge	FW-2-3	0.3	FW-2-3 FW-2-3 G	64-2345 32-234 51-G-887
2.5 mm	12-1/2 gauge	FW-2-3 3/4"	0.5	FW-2-3 FW-2-3 G	64-2345 32-234 51-G-887
1.9 mm	14-1/2 gauge	FW-1-2	0.1	FW-1-2	64-2345
1.7 mm	15-1/2 gauge	FW-1-2	0.1	FW-1-2	64-2345
2.5 mm barbed	12-1/2 barbed	FW-4-5	1.0	FW-4-5	64-2345
2.2 mm barbed	13-1/2 barbed	FW-4-5	1.0	FW-4-5	64-2345
2.0 mm barbed	14 barbed	FW-3-4	0.8	FW-3-4	64-2345
1.7 mm barbed	15-1/2 barbed	FW-3-4	0.8	FW-3-4	64-2345

BUTT TYPE FENCE WIRE SLEEVES					
NICOPRESS® SLEEVE SELECTION				NICOPRESS® TOOLS	
METRIC WIRE SIZE (mm)	WIRE SIZE	SLEEVE STOCK NUMBER	APPROX. WT (Kg) BOX OF 100	TOOL GROOVE	TOOLS
4.5 mm	7 gauge	2-3/081-M	4.8	FW-3-4 M	64-2345 51-MJ
3.7 mm	9 gauge	2-148-J	1.8	J	31-CJ 31-DJ
3.4 mm	10 gauge	2-134-J	1.7	J	31-CJ 31-DJ
3.0 mm	11 gauge	2-120-J	1.7	J	31-CJ 31-DJ
2.5 mm	12-1/2 gauge	5-109-D135	1.0	D	31-DJ 31-DC
2.0 mm	14-1/2 gauge	5-083-C	0.5	C	31-DC 31-CJ
2.5 mm	12-1/2 barbed	125-JFW	1.8	J	31-DJ 31-CJ
2.2 mm	13-1/2 barbed	135-JFW	2.0	J	31-DJ 31-CJ
2.0 mm	14 barbed	140-JFW	1.7	J	31-DJ 31-CJ



FENCE WIRE SLEEVES AND TOOLS—DATA SHEET

FENCE TAPS					
NICOPRESS® FENCE TAP SELECTION				NICOPRESS® TOOLS	
FENCE TAP STOCK NUMBE	FENCE WIRE SIZE	TAP WIRE SIZE	APPROX. WT (Kg) BOX OF 100	TOOL GROOVE	TOOL STOCK NO.
FWT-3-4 For smooth, solid fence wire (electrified)	12-1/2 gauge (2.5 mm)	12 to 14-1/2 gauge (2.0 mm)	0.2	FW-3-4 FWT-3-4*	64-2345 32-234
FWT-4-5 For barbed wire	12-1/2 to 15-1/2 gauge (2.5 to 1.7 mm)	6 to 12 gauge (2.0 to 4.0 mm)	0.3	FW-4-5	64-2345

*32-234 for 12-1/2 Ga. Wire ONLY, FWT-3-4 tool die groove, 2 overlapped presses per tap.

SPLIT SPLICING SLEEVES							
WIRE SIZE/TYPE						NICOPRESS® TOOLS	
SPLIT SLEEVE STOCK NO.	SMOOTH, SOLID AND WOVEN	HIGH TENSILE	STANDARD BARBED	HIGH TENSILE BARBED	APPROX. WT (Kg) BOX OF 100	TOOL GROOVE	TOOL STOCK NO.
FS-2-3	12-1/2 gauge (2.5 mm)	12-1/2 gauge (2.5 mm)	—	—	0.3	FW-2-3	64-2345
FS-3-4	10 gauge (3.4 mm) 11 gauge (3.0 mm)	—	14 gauge (2.0 mm)	15-1/2 gauge (1.7 mm)	0.5	FW-3-4	64-2345

NICOPRESS® TOOL WEIGHT INFORMATION			
MODEL NO.	WT. (Kg)	MODEL NO.	WT. (Kg)
64-2345	3.2	32-234	1.1
51-G-887	2.3	31-DC	1.1
51-MJ	2.3	31-DJ	1.1
3-56	5.9	31-CJ	1.1